Rapid connection.

Geberit discharge pipes made of polyethylene (PE) can be connected to one another in a permanent and impermeable manner using, for example, an electrofusion coupler or an electrofusion coupling with integrated thermal fuse. Geberit has developed new tools to help speed up and facilitate the related work on the construction site or in the workshop.

Geberit pipe scraper



Before welding, the surfaces of the pipe ends have to be scraped as only then can an optimal connection be guaranteed. When it comes to scraping, plumbers often use a robust knife blade. Thanks to the new Geberit pipe scraper, this process is now considerably safer and only requires around a third of the time.

- → Enables a safe, quick and precise scraping of pipe ends
- → For pipe diameters of between 63 and 160 mm
- → Convenient handling, light and compact design

Geberit electrofusion machine

Whether an electrofusion coupler or a coupling with integrated thermal fuse, the new electrofusion machine is suitable for all applications and pipe dimensions. The machine is easy to use, powerful and makes work on the construction site easier thanks to the remote control. The overvoltage protection, which is built in as standard, ensures safe operation at all times – even when the power is supplied by a generator.

- → Suitable for all Geberit polyethylene pipes and fittings
- → Simultaneous welding of up to three electrofusion couplers
- → Comes with a remote control, overvoltage protection and a robust plastic box



