

Cleverly planned and pre-assembled

The Geberit shower surface Setaplano

The new Geberit shower surface Setaplano is made of a high-quality mineral composite material whose surface has a silky smooth and warm feel, features excellent non-slip properties and is also easy to clean. With the number of individual parts that need to be installed kept to a minimum, the plumber too has every reason to be delighted.

While conventional installation sets for floor-even shower surfaces sometimes contain up to 90 individual parts, the number of parts is kept to a minimum with the new Geberit shower surface Setaplano. In other words, as many components as possible are pre-assembled at the factory. Having only few parts has a lot of advantages on the building site – the preparation work on site is completed in next to no time, and the overall time required for installation is reduced.

Sealed at the factory

Pre-assembly simplifies the work of the plumber while also ensuring the greatest possible reliability. Like with the Geberit shower drains and channels for tile-bearing floor-even showers, the sealing foil is already applied to the Geberit shower surface Setaplano at the factory. A clever solution that prevents possible handling errors and fits every installation type was developed for the particularly tricky areas in the corners.

Stable and a plumber's dream



↑ The new Geberit shower surface Setaplano is made of a high-quality mineral composite material whose surface has a silky smooth and warm feel and is easy to clean. With the drain positioned to one side, Setaplano offers maximum freedom – nothing gets in the way of the perfect showering experience.



← Pre-assembly simplifies the work of the plumber. The sealing foil applied at the factory is a reliable solution.

The unmistakable blue installation frame is made of powder-coated steel. Depending on the size of the Geberit shower surface Setaplano, four or six feet are required for installation. These can be easily clicked into the installation frame at the designated points and then fixed to the unfinished floor. The alignment to the floor height can then be comfortably carried out from above using a standard tool. Once the right height has been found, the structure can be reliably locked into place using sliders.

A flexible trap

The Geberit shower surface Setaplano features a new, easy-to-clean trap that is available in two versions: with a depth of water seal of 30 mm and a discharge capacity of over 0.5 litres per second, or with a depth of water seal of 50 mm and a discharge capacity of over 0.65 litres per second. Both versions can be turned 360 degrees after they have been inserted into the installation frame and can therefore be aligned as required. Because a bracket is already pre-mounted on the frame, the trap only has to be clicked into place. The trap cup, which is made of easy-care, elastic plastic, proves extremely useful when it comes to subsequent maintenance: It can be removed in its entirety with a flick of the wrist, meaning that cleaning couldn't be simpler.

The Geberit shower surface Setaplano will be available in stores in a range of sizes from April 2017. ←

In brief

- Installation height (from unfinished floor to upper edge of shower surface): 60–250 mm
- Discharge capacity: 0.5 l/s (depth of water seal 30 mm), 0.65 l/s (depth of water seal 50 mm)
- Meets the standards DIN 4109, VDI 4100, SIA 181 (sound insulation)



↑ The feet are easily clicked into the installation frame. The alignment to the floor height can then be comfortably carried out from above.



↑ Once the right height has been found, the feet can be reliably fixed into place using sliders.



↑ The trap only has to be clicked into place in the pre-mounted bracket.